



09/885 092

cofc

PATENT  
Customer No. 22,852  
Attorney Docket No. 07040.0089

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re U.S. Patent No.: 6,972,063 B2 )  
Inventors: Renato CARETTA et al. )  
Issue Date.: December 6, 2005 )  
For: METHOD OF MANUFACTURING A )  
A TIRE FOR A VEHICLE WHEEL )

**Certificate**  
**JAN 27 2006**  
**of Correction**

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Sir:

REQUEST FOR CERTIFICATE OF CORRECTION

Pursuant to 35 U.S.C. 254 and 37 C.F.R. 1.322, this is a request for the issuance of a Certificate of Correction in the above-identified patent. Two (2) copies of PTO Form 1050 are appended. The complete Certificate of Correction involves one (1) page.

The mistake identified in the attached form occurred through the fault of the Patent Office, as clearly disclosed by the records of the application which matured into this patent. Issuance of the Certificate of Correction containing the correction is earnestly requested.

If it should be determined that the mistake resulted from an error made in good faith by the applicants, then, pursuant to 35 U.S.C. 255 and 37 C.F.R. 1.323, it is requested that a Certificate of Correction be issued correcting this mistake. Under such circumstances, it is requested that the fee set forth in 37 C.F.R. 1.20(a) and any

JAN 30 2006

additional fees needed be charged to our Deposit Account No. 06-0916, for which authorization is hereby given.


Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,  
GARRETT & DUNNER, L.L.P.

Dated:

JAN 25 2006

By:

  
Ernest F. Chapman  
Reg. No. 25,961

JAN 30 2006

**UNITED STATES PATENT AND TRADEMARK OFFICE**  
**CERTIFICATE OF CORRECTION**

PATENT NO. 6,972,063 B2  
DATED: December 6, 2005  
INVENTORS: Renato CARETTA et al.

It is hereby certified that errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page, Item (57), delete the Abstract in its entirety and replace it with the following abstract:

--A method of manufacturing a tyre for a vehicle wheel includes making at least one carcass ply by deposition of elongated sections circumferentially distributed on a toroidal support and applying annular reinforcing structures to a region close to inner-circumferential edges of the at least one carcass ply. Each of the elongated sections extends in a U-shaped configuration around a cross-sectional outline of the toroidal support to define two side portions and one crown portion. The side portions are mutually spaced apart in an axial direction of the toroidal support. The crown portion extends at a radially-outer position between the side portions. Each elongated section is laid down substantially in a plane parallelly offset relative to a meridian plane of the toroidal support.--.

MAILING ADDRESS OF SENDER

Finnegan, Henderson, Farabow,  
Garrett & Dunner, L.L.P.  
901 New York Avenue, NW  
Washington, D.C. 20001-4413

Patent No. 6,972,063 B2

No. of additional copies  
@ 50¢ per page

JAN 21 2006

**UNITED STATES PATENT AND TRADEMARK OFFICE**  
**CERTIFICATE OF CORRECTION**

PATENT NO.            6,972,063 B2  
DATED:                December 6, 2005  
INVENTORS:           Renato CARETTA et al.

It is hereby certified that errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page, Item (57), delete the Abstract in its entirety and replace it with the following abstract:

--A method of manufacturing a tyre for a vehicle wheel includes making at least one carcass ply by deposition of elongated sections circumferentially distributed on a toroidal support and applying annular reinforcing structures to a region close to inner-circumferential edges of the at least one carcass ply. Each of the elongated sections extends in a U-shaped configuration around a cross-sectional outline of the toroidal support to define two side portions and one crown portion. The side portions are mutually spaced apart in an axial direction of the toroidal support. The crown portion extends at a radially-outer position between the side portions. Each elongated section is laid down substantially in a plane parallelly offset relative to a meridian plane of the toroidal support.--.

MAILING ADDRESS OF SENDER

Finnegan, Henderson, Farabow,  
Garrett & Dunner, L.L.P.  
901 New York Avenue, NW  
Washington, D.C. 20001-4413

Patent No. 6,972,063 B2

No. of additional copies  
@ 50¢ per page

---